

**lincom** — Linear combinations of estimators

[Syntax](#)  
[Remarks and examples](#)
[Menu](#)  
[Stored results](#)
[Description](#)  
[References](#)
[Options](#)  
[Also see](#)

## Syntax

```
lincom exp [ , options ]
```

<i>options</i>	Description
<a href="#"><u>e</u>form</a>	generic label; <code>exp(b)</code>
<a href="#"><u>o</u>r</a>	odds ratio
<a href="#"><u>h</u>r</a>	hazard ratio
<a href="#"><u>s</u>hr</a>	subhazard ratio
<a href="#"><u>i</u>rr</a>	incidence-rate ratio
<a href="#"><u>r</u>rr</a>	relative-risk ratio
<a href="#"><u>l</u>evel(#)</a>	set confidence level; default is <code>level(95)</code>
<a href="#"><i>display_options</i></a>	control column formats
<a href="#"><u>d</u>f(#)</a>	use <i>t</i> distribution with # degrees of freedom for computing <i>p</i> -values and confidence intervals

*exp* is any linear combination of coefficients that is a valid syntax for `test`; see [\[R\] test](#). *exp* must not contain an equal sign.

`df(#)` does not appear in the dialog box.

## Menu

Statistics > Postestimation > Linear combinations of estimates

## Description

`lincom` computes point estimates, standard errors, *t* or *z* statistics, *p*-values, and confidence intervals for linear combinations of coefficients after any estimation command. Results can optionally be displayed as odds ratios, hazard ratios, incidence-rate ratios, or relative-risk ratios.

`lincom` can be used with `svy` estimation results; see [\[SVY\] svy postestimation](#).

## Options

`eform`, `or`, `hr`, `shr`, `irr`, and `rrr` all report coefficient estimates as  $\exp(\hat{\beta})$  rather than  $\hat{\beta}$ . Standard errors and confidence intervals are similarly transformed. `or` is the default after `logistic`. The only difference in these options is how the output is labeled.

Option	Label	Explanation	Example commands
<code>eform</code>	<code>exp(b)</code>	Generic label	<code>cloglog</code>
<code>or</code>	Odds Ratio	Odds ratio	<code>logistic</code> , <code>logit</code>
<code>hr</code>	Haz. Ratio	Hazard ratio	<code>stcox</code> , <code>streg</code>
<code>shr</code>	SHR	Subhazard ratio	<code>stcrreg</code>
<code>irr</code>	IRR	Incidence-rate ratio	<code>poisson</code>
<code>rrr</code>	RRR	Relative-risk ratio	<code>mlogit</code>

`exp` may not contain any additive constants when you use the `eform`, `or`, `hr`, `irr`, or `rrr` option. `level(#)` specifies the confidence level, as a percentage, for confidence intervals. The default is `level(95)` or as set by `set level`; see [U] 20.7 **Specifying the width of confidence intervals**. `display_options`: `cformat(%fmt)`, `pformat(%fmt)`, and `sformat(%fmt)`; see [R] **estimation options**.

The following option is available with `lincom` but is not shown in the dialog box:

`df(#)` specifies that the  $t$  distribution with  $\#$  degrees of freedom be used for computing  $p$ -values and confidence intervals. The default is to use `e(df_r)` degrees of freedom or the standard normal distribution if `e(df_r)` is missing.

## Remarks and examples

[stata.com](https://www.stata.com)

Remarks are presented under the following headings:

[Using lincom](#)  
[Odds ratios and incidence-rate ratios](#)  
[Multiple-equation models](#)

## Using lincom

After fitting a model and obtaining estimates for coefficients  $\beta_1, \beta_2, \dots, \beta_k$ , you may want to view estimates for linear combinations of the  $\beta_i$ , such as  $\beta_1 - \beta_2$ . `lincom` can display estimates for any linear combination of the form  $c_0 + c_1\beta_1 + c_2\beta_2 + \dots + c_k\beta_k$ .

`lincom` works after any estimation command for which `test` works. Any valid expression for `test` syntax 1 (see [R] **test**) is a valid expression for `lincom`.

`lincom` is useful for viewing odds ratios, hazard ratios, etc., for one group (that is, one set of covariates) relative to another group (that is, another set of covariates). See the examples below.

## ▷ Example 1

We perform a linear regression:

```
. use http://www.stata-press.com/data/r13/regress
. regress y x1 x2 x3
```

Source	SS	df	MS			
Model	3259.3561	3	1086.45203	Number of obs = 148		
Residual	1627.56282	144	11.3025196	F( 3, 144) = 96.12		
				Prob > F = 0.0000		
				R-squared = 0.6670		
				Adj R-squared = 0.6600		
Total	4886.91892	147	33.2443464	Root MSE = 3.3619		

  

y	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
x1	1.457113	1.07461	1.36	0.177	-.666934	3.581161
x2	2.221682	.8610358	2.58	0.011	.5197797	3.923583
x3	-.006139	.0005543	-11.08	0.000	-.0072345	-.0050435
_cons	36.10135	4.382693	8.24	0.000	27.43863	44.76407

To see the difference of the coefficients of x2 and x1, we type

```
. lincom x2 - x1
( 1) - x1 + x2 = 0
```

y	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
(1)	.7645682	.9950282	0.77	0.444	-1.20218	2.731316

The expression can be any linear combination.

```
. lincom 3*x1 + 500*x3
( 1) 3*x1 + 500*x3 = 0
```

y	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
(1)	1.301825	3.396624	0.38	0.702	-5.411858	8.015507

Nonlinear expressions are not allowed.

```
. lincom x2/x1
not possible with test
r(131);
```

For information about estimating nonlinear expressions, see [\[R\] nlcom](#).



## □ Technical note

lincom uses the same shorthands for coefficients as does test (see [\[R\] test](#)). When you type x1, for instance, lincom knows that you mean the coefficient of x1. The formal syntax for referencing this coefficient is actually `_b[x1]`, or alternatively, `_coef[x1]`. So, more formally, in the last example we could have typed

```
. lincom 3*_b[x1] + 500*_b[x3]
(output omitted)
```



**Odds ratios and incidence-rate ratios**

After logistic regression, the `or` option can be specified with `lincom` to display odds ratios for any effect. Incidence-rate ratios after commands such as `poisson` can be similarly obtained by specifying the `irr` option.

▷ **Example 2**

Consider the low birthweight dataset from [Hosmer, Lemeshow, and Sturdivant \(2013, 24\)](#). We fit a logistic regression model of low birthweight (variable `low`) on the following variables:

Variable	Description	Coding
<code>age</code>	age in years	
<code>race</code>	race	1 if white, 2 if black, 3 if other
<code>smoke</code>	smoking status	1 if smoker, 0 if nonsmoker
<code>ht</code>	history of hypertension	1 if yes, 0 if no
<code>ui</code>	uterine irritability	1 if yes, 0 if no
<code>lwd</code>	maternal weight before pregnancy	1 if weight < 110 lb., 0 otherwise
<code>ptd</code>	history of premature labor	1 if yes, 0 if no
<code>c.age##lwd</code>	age main effects, lwd main effects, and their interaction	
<code>smoke##lwd</code>	smoke main effects, lwd main effects, and their interaction	

We first fit a model without the interaction terms by using `logit`.

```
. use http://www.stata-press.com/data/r13/lbw3
(Hosmer & Lemeshow data)

. logit low age lwd i.race smoke ptd ht ui
Iteration 0:  log likelihood =  -117.336
Iteration 1:  log likelihood =  -99.3982
Iteration 2:  log likelihood = -98.780418
Iteration 3:  log likelihood = -98.777998
Iteration 4:  log likelihood = -98.777998

Logistic regression                               Number of obs   =       189
                                                    LR chi2(8)      =       37.12
                                                    Prob > chi2     =       0.0000
Log likelihood = -98.777998                       Pseudo R2      =       0.1582
```

	low	Coef.	Std. Err.	z	P> z	[95% Conf. Interval]
	<code>age</code>	-.0464796	.0373888	-1.24	0.214	-.1197603 .0268011
	<code>lwd</code>	.8420615	.4055338	2.08	0.038	.0472299 1.636893
	<code>race</code>					
	<code>black</code>	1.073456	.5150753	2.08	0.037	.0639273 2.082985
	<code>other</code>	.815367	.4452979	1.83	0.067	-.0574008 1.688135
	<code>smoke</code>	.8071996	.404446	2.00	0.046	.0145001 1.599899
	<code>ptd</code>	1.281678	.4621157	2.77	0.006	.3759478 2.187408
	<code>ht</code>	1.435227	.6482699	2.21	0.027	.1646414 2.705813
	<code>ui</code>	.6576256	.4666192	1.41	0.159	-.2569313 1.572182
	<code>_cons</code>	-1.216781	.9556797	-1.27	0.203	-3.089878 .656317

To get the odds ratio for black smokers relative to white nonsmokers (the reference group), we type

```
. lincom 2.race + smoke, or
( 1) [low]2.race + [low]smoke = 0
```

low	Odds Ratio	Std. Err.	z	P> z	[95% Conf. Interval]	
(1)	6.557805	4.744692	2.60	0.009	1.588176	27.07811

lincom computed  $\exp(\beta_{2.race} + \beta_{smoke}) = 6.56$ . To see the odds ratio for white smokers relative to black nonsmokers, we type

```
. lincom smoke - 2.race, or
( 1) - [low]2.race + [low]smoke = 0
```

low	Odds Ratio	Std. Err.	z	P> z	[95% Conf. Interval]	
(1)	.7662425	.4430176	-0.46	0.645	.2467334	2.379603

Now let's add the interaction terms to the model (Hosmer and Lemeshow 1989, table 4.10). This time, we will use logistic rather than logit. By default, logistic displays odds ratios.

```
. logistic low i.race ht ui ptd c.age##lwd smoke##lwd
Logistic regression                               Number of obs =      189
                                                    LR chi2(10)      =      42.66
                                                    Prob > chi2     =      0.0000
Log likelihood = -96.00616                       Pseudo R2       =      0.1818
```

low	Odds Ratio	Std. Err.	z	P> z	[95% Conf. Interval]	
race						
black	2.95383	1.532789	2.09	0.037	1.068277	8.167465
other	2.137589	.9919138	1.64	0.102	.8608708	5.307752
ht	3.893141	2.575201	2.05	0.040	1.064768	14.2346
ui	2.071284	.9931388	1.52	0.129	.8092926	5.301192
ptd	3.426633	1.615282	2.61	0.009	1.360252	8.632089
age	.9194513	.041896	-1.84	0.065	.8408967	1.005344
1.lwd	.1772934	.3312384	-0.93	0.354	.0045539	6.902367
lwd#c.age						
1	1.15883	.09602	1.78	0.075	.9851215	1.36317
smoke						
smoker	3.168096	1.452378	2.52	0.012	1.289956	7.78076
smoke#lwd						
smoker 1	.2447849	.2003996	-1.72	0.086	.0491956	1.217988
_cons	.599443	.6519163	-0.47	0.638	.0711271	5.051971

Hosmer and Lemeshow (1989, table 4.13) consider the effects of smoking (smoke = 1) and low maternal weight before pregnancy (lwd = 1). The effect of smoking among non-low-weight mothers (lwd = 0) is given by the odds ratio 3.17 for smoke in the logistic output. The effect of smoking among low-weight mothers is given by

```
. lincom 1.smoke + 1.smoke#1.lwd
( 1) [low]1.smoke + [low]1.smoke#1.lwd = 0
```

low	Odds Ratio	Std. Err.	z	P> z	[95% Conf. Interval]
(1)	.7755022	.574951	-0.34	0.732	.1813465 3.316323

We did not have to specify the `or` option. After `logistic`, `lincom` assumes `or` by default.

The effect of low weight (`lwd = 1`) is more complicated because we fit an `age × lwd` interaction. We must specify the age of mothers for the effect. The effect among 30-year-old nonsmokers is given by

```
. lincom 1.lwd + 30*1.lwd#c.age
( 1) [low]1.lwd + 30*[low]1.lwd#c.age = 0
```

low	Odds Ratio	Std. Err.	z	P> z	[95% Conf. Interval]
(1)	14.7669	13.5669	2.93	0.003	2.439264 89.39633

`lincom` computed  $\exp(\beta_{1\text{lwd}} + 30\beta_{\text{age}1\text{lwd}}) = 14.8$ . It may seem odd that we entered it as `1.lwd + 30*1.lwd#c.age`, but remember that these terms are just `lincom`'s (and `test`'s) shorthands for `_b[1.lwd]` and `_b[1.lwd#c.age]`. We could have typed

```
. lincom _b[1.lwd] + 30*_b[1.lwd#c.age]
( 1) [low]1.lwd + 30*[low]1.lwd#c.age = 0
```

low	Odds Ratio	Std. Err.	z	P> z	[95% Conf. Interval]
(1)	14.7669	13.5669	2.93	0.003	2.439264 89.39633

◀

## Multiple-equation models

`lincom` also works with multiple-equation models. The only difference is how you refer to the coefficients. Recall that for multiple-equation models, coefficients are referenced using the syntax

`[eqno]varname`

where `eqno` is the equation number or equation name and `varname` is the corresponding variable name for the coefficient; see [U] [13.5 Accessing coefficients and standard errors](#) and [R] [test](#) for details.

## ▷ Example 3

Let's consider [example 4](#) from [R] [mlogit](#) (Tarlov et al. 1989; Wells et al. 1989).

```
. use http://www.stata-press.com/data/r13/sysdsn1
(Health insurance data)
```

```
. mlogit insure age male nonwhite i.site, nolog
```

```
Multinomial logistic regression      Number of obs   =      615
                                      LR chi2(10)      =      42.99
                                      Prob > chi2      =      0.0000
Log likelihood = -534.36165           Pseudo R2       =      0.0387
```

insure	Coef.	Std. Err.	z	P> z	[95% Conf. Interval]	
Indemnity (base outcome)						
Prepaid						
age	-.011745	.0061946	-1.90	0.058	-.0238862	.0003962
male	.5616934	.2027465	2.77	0.006	.1643175	.9590693
nonwhite	.9747768	.2363213	4.12	0.000	.5115955	1.437958
site						
2	.1130359	.2101903	0.54	0.591	-.2989296	.5250013
3	-.5879879	.2279351	-2.58	0.010	-1.034733	-.1412433
_cons	.2697127	.3284422	0.82	0.412	-.3740222	.9134476
Uninsure						
age	-.0077961	.0114418	-0.68	0.496	-.0302217	.0146294
male	.4518496	.3674867	1.23	0.219	-.268411	1.17211
nonwhite	.2170589	.4256361	0.51	0.610	-.6171725	1.05129
site						
2	-1.211563	.4705127	-2.57	0.010	-2.133751	-.2893747
3	-.2078123	.3662926	-0.57	0.570	-.9257327	.510108
_cons	-1.286943	.5923219	-2.17	0.030	-2.447872	-.1260134

To see the estimate of the sum of the coefficient of male and the coefficient of nonwhite for the Prepaid outcome, we type

```
. lincom [Prepaid]male + [Prepaid]nonwhite
( 1) [Prepaid]male + [Prepaid]nonwhite = 0
```

insure	Coef.	Std. Err.	z	P> z	[95% Conf. Interval]	
(1)	1.53647	.3272489	4.70	0.000	.8950741	2.177866

To view the estimate as a ratio of relative risks (see [\[R\] mlogit](#) for the definition and interpretation), we specify the `rrr` option.

```
. lincom [Prepaid]male + [Prepaid]nonwhite, rrr
( 1) [Prepaid]male + [Prepaid]nonwhite = 0
```

insure	RRR	Std. Err.	z	P> z	[95% Conf. Interval]	
(1)	4.648154	1.521103	4.70	0.000	2.447517	8.827451

◀

## Stored results

`lincom` stores the following in `r()`:

Scalars

```
r(estimate) point estimate
r(se)        estimate of standard error
r(df)        degrees of freedom
```

## References

- Hosmer, D. W., Jr., and S. A. Lemeshow. 1989. *Applied Logistic Regression*. New York: Wiley.
- Hosmer, D. W., Jr., S. A. Lemeshow, and R. X. Sturdivant. 2013. *Applied Logistic Regression*. 3rd ed. Hoboken, NJ: Wiley.
- Tarlov, A. R., J. E. Ware, Jr., S. Greenfield, E. C. Nelson, E. Perrin, and M. Zubkoff. 1989. The medical outcomes study. An application of methods for monitoring the results of medical care. *Journal of the American Medical Association* 262: 925–930.
- Wells, K. B., R. D. Hays, M. A. Burnam, W. H. Rogers, S. Greenfield, and J. E. Ware, Jr. 1989. Detection of depressive disorder for patients receiving prepaid or fee-for-service care. Results from the Medical Outcomes Survey. *Journal of the American Medical Association* 262: 3298–3302.

## Also see

- [\[R\] nlcom](#) — Nonlinear combinations of estimators
- [\[R\] test](#) — Test linear hypotheses after estimation
- [\[R\] testnl](#) — Test nonlinear hypotheses after estimation
- [\[U\] 13.5 Accessing coefficients and standard errors](#)
- [\[U\] 20 Estimation and postestimation commands](#)