

**texdoc 2.0**  
**An update on creating LaTeX documents from within Stata**

**Example 1**

Ben Jann  
University of Bern, ben.jann@soz.unibe.ch

UK Stata Users Group meeting  
London, September 89, 2016

**Contents**

<b>1</b>	<b>The texdoc source file</b>	<b>2</b>
<b>2</b>	<b>The resulting <math>\LaTeX</math> source file</b>	<b>5</b>
<b>3</b>	<b>The resulting PDF</b>	<b>7</b>

# 1 The texdoc source file

— *the-auto-data.texdoc* —

```
texdoc init the-auto-data, replace logdir(log) ///  
    gropts(optargs(width=0.8\textwidth))  
set linesize 100  
  
/**/  
\documentclass[12pt]{article}  
\usepackage{fullpage}  
\usepackage{hyperref,graphicx,booktabs,dcolumn}  
\usepackage{stata}  
  
\title{The Auto Data}  
\author{Ben Jann}  
\date{\today}  
  
\begin{document}  
  
\maketitle  
  
\begin{abstract}  
    I really like the auto data because it is so awesome. You can do all kinds  
    of stuff with the auto data, like tabulating a variable or computing  
    descriptive statistics. You can even use the auto data to estimate  
    regression models. I am really amazed by the richness of this dataset.  
    There is information on many different makes and models and you can learn,  
    for example, about the gear ratio of a Dodge Diplomat (a stunning 2.47). In  
    this article I will illustrate the auto data and I will show you what you  
    can do with it. I am convinced that you will love this dataset as much as I  
    do after having read this paper.  
\end{abstract}  
  
\tableofcontents  
  
\section{Introduction}  
  
What we want to do in the introductory section is to open the data and have a  
look at what is inside of it. Since the auto data is shipped with Stata, we can  
use the \stcmd{sysuse} command to open it (see \dref{sysuse}). Furthermore, the  
\stcmd{describe} command will list the variables and display some other  
information (see \dref{describe}). So let's start:  
  
***/  
  
texdoc stlog  
    sysuse auto  
    texdoc stlog cnp  
    describe  
texdoc stlog close
```

```

/****

Wow!
****/
texdoc write `r(N)' observations!
/****
And what a wealth of variables! Make, price, miles per gallon, and many more. I
am very motivated to learn more about this amazing data set.

\section{Descriptives}

Let's now look at some descriptive statistics. Maybe also let's
do a graph.

****/

texdoc stlog
  summarize
  pspline price weight
texdoc stlog close
texdoc graph, label(fig1) caption(What a crazy relation between price and weight)

texdoc write \def\myvalue{\=stroofreal(r(gof_p),"%9.3f")'}

/****

In figure~\ref{fig1} we see that for some unknown reason expensive cars seem to
be heavier. Furthermore, the relation appears to be nonlinear, as the pilot
goodness-of-fit test rejects the linear fit with a p-value of \myvalue.

\begin{quote}\small
Actually, I really only want to print a graph without printing the code that
produced the code. Hm, how can we do that? Maybe the \stcmd{nolog} option will
do.
\end{quote}

****/

texdoc stlog, nolog
  pspline price mpg
texdoc stlog close
texdoc graph, label(fig2) caption(Another crazy relation)

/****

In figure~\ref{fig2} we see that price is also related to miles per gallon. How
interesting!

\section{Regression tables}

Finally we get to regressions! In table~\ref{table1} we see that an additional

```

pound of car costs around 3.5 dollars once we control for milage and origin.

\*\*\*/

```
texdoc stlog, nolog
  sysuse auto
  regress price weight
  estimates store m1
  regress price weight mpg
  estimates store m2
  regress price weight mpg foreign
  estimates store m3
  esttab m1 m2 m3 using log/table1.tex, replace se label ///
    nomtitles booktabs align(D{.}{.}{-1}) ///
    title(Some regression table\label{table1})
texdoc stlog close
texdoc write \input{log/table1.tex}
```

/\*\*\*

\end{document}

\*\*\*/

— end of file —

## 2 The resulting L<sup>A</sup>T<sub>E</sub>X source file

Applying

```
. texdoc do the-auto-data.texdoc
```

generates to the following L<sup>A</sup>T<sub>E</sub>X file.

— *the-auto-data.tex* —

```
\documentclass[12pt]{article}
\usepackage{fullpage}
\usepackage{hyperref,graphicx,booktabs,dcolumn}
\usepackage{stata}

\title{The Auto Data}
\author{Ben Jann}
\date{\today}

\begin{document}

\maketitle

\begin{abstract}
  I really like the auto data because it is so awesome. You can do all kinds
  of stuff with the auto data, like tabulating a variable or computing
  descriptive statistics. You can even use the auto data to estimate
  regression models. I am really amazed by the richness of this dataset.
  There is information on many different makes and models and you can learn,
  for example, about the gear ratio of a Dodge Diplomat (a stunning 2.47). In
  this article I will illustrate the auto data and I will show you what you
  can do with it. I am convinced that you will love this dataset as much as I
  do after having read this paper.
\end{abstract}

\tableofcontents

\section{Introduction}

What we want to do in the introductory section is to open the data and have a
look at what is inside of it. Since the auto data is shipped with Stata, we can
use the \stcmd{sysuse} command to open it (see \dref{sysuse}). Furthermore, the
\stcmd{describe} command will list the variables and display some other
information (see \dref{describe}). So let's start:

\begin{stlog}\input{log/1.log.tex}\end{stlog}

Wow!
74 observations!
And what a wealth of variables! Make, price, miles per gallon, and many more. I
am very motivated to learn more about this amazing data set.

\section{Descriptives}
```

Let's now look at some descriptive statistics. Maybe also let's do a graph.

```
\begin{stlog}\input{log/2.log.tex}\end{stlog}
\begin{figure}
  \centering
  \includegraphics[width=0.8\textwidth]{log/2}
  \caption{What a crazy relation between price and weight}
  \label{fig1}
\end{figure}
\def\myvalue{0.009}
```

In figure~\ref{fig1} we see that for some unknown reason expensive cars seem to be heavier. Furthermore, the relation appears to be nonlinear, as the pilot goodness-of-fit test rejects the linear fit with a p-value of \myvalue.

```
\begin{quote}\small
Actually, I really only want to print a graph without printing the code that produced the code. Hm, how can we do that? Maybe the \stcmd{nolog} option will do.
\end{quote}
```

```
\begin{figure}
  \centering
  \includegraphics[width=0.8\textwidth]{log/3}
  \caption{Another crazy relation}
  \label{fig2}
\end{figure}
```

In figure~\ref{fig2} we see that price is also related to miles per gallon. How interesting!

```
\section{Regression tables}
```

Finally we get to regressions! In table~\ref{table1} we see that an additional pound of car costs around 3.5 dollars once we control for milage and origin.

```
\input{log/table1.tex}
```

```
\end{document}
```

— *end of file* —

### 3 The resulting PDF

The following pages display the resulting PDF after compiling the  $\text{\LaTeX}$  source file.

# The Auto Data

Ben Jann

September 8, 2016

## Abstract

I really like the auto data because it is so awesome. You can do all kinds of stuff with the auto data, like tabulating a variable or computing descriptive statistics. You can even use the auto data to estimate regression models. I am really amazed by the richness of this dataset. There is information on many different makes and models and you can learn, for example, about the gear ratio of a Dodge Diplomat (a stunning 2.47). In this article I will illustrate the auto data and I will show you what you can do with it. I am convinced that you will love this dataset as much as I do after having read this paper.

## Contents

1	Introduction	1
2	Descriptives	2
3	Regression tables	4

## 1 Introduction

What we want to do in the introductory section is to open the data and have a look at what is inside of it. Since the auto data is shipped with Stata, we can use the `sysuse` command to open it (see [D] `sysuse`). Furthermore, the `describe` command will list the variables and display some other information (see [D] `describe`). So let's start:

```
. sysuse auto
(1978 Automobile Data)
```

```
. describe
Contains data from /Applications/Stata14/ado/base/a/auto.dta
  obs:          74          1978 Automobile Data
  vars:         12          29 Jul 2016 15:41
  size:        3,182          (_dta has notes)
```

---

variable name	storage type	display format	value label	variable label
make	str18	%-18s		Make and Model
price	int	%8.0gc		Price
mpg	int	%8.0g		Mileage (mpg)
rep78	int	%8.0g		Repair Record 1978
headroom	float	%6.1f		Headroom (in.)
trunk	int	%8.0g		Trunk space (cu. ft.)
weight	int	%8.0gc		Weight (lbs.)
length	int	%8.0g		Length (in.)
turn	int	%8.0g		Turn Circle (ft.)
displacement	int	%8.0g		Displacement (cu. in.)
gear_ratio	float	%6.2f		Gear Ratio
foreign	byte	%8.0g	origin	Car type

---

```
Sorted by: foreign
```

Wow! 74 observations! And what a wealth of variables! Make, price, miles per gallon, and many more. I am very motivated to learn more about this amazing data set.

## 2 Descriptives

Let's now look at some descriptive statistics. Maybe also let's do a graph.

```
. summarize
```

Variable	Obs	Mean	Std. Dev.	Min	Max
make	0				
price	74	6165.257	2949.496	3291	15906
mpg	74	21.2973	5.785503	12	41
rep78	69	3.405797	.9899323	1	5
headroom	74	2.993243	.8459948	1.5	5
trunk	74	13.75676	4.277404	5	23
weight	74	3019.459	777.1936	1760	4840
length	74	187.9324	22.26634	142	233
turn	74	39.64865	4.399354	31	51
displacement	74	197.2973	91.83722	79	425
gear_ratio	74	3.014865	.4562871	2.19	3.89
foreign	74	.2972973	.4601885	0	1

```
. pspline price weight
(pilot goodness-of-fit chi2(16) = 32.38; p = 0.0089)
(using penalized model ...)
```

In figure 1 we see that for some unknown reason expensive cars seem to be heavier. Furthermore, the relation appears to be nonlinear, as the pilot goodness-of-fit test rejects the linear fit with a p-value of 0.009.

Actually, I really only want to print a graph without printing the code that produced the code. Hm, how can we do that? Maybe the `nolog` option will do.

In figure 2 we see that price is also related to miles per gallon. How interesting!




Figure 1: What a crazy relation between price and weight




Figure 2: Another crazy relation

### 3 Regression tables

Finally we get to regressions! In table 1 we see that an additional pound of car costs around 3.5 dollars once we control for milage and origin.

Table 1: Some regression table

	(1)	(2)	(3)
Weight (lbs.)	2.044*** (0.377)	1.747** (0.641)	3.465*** (0.631)
Mileage (mpg)		-49.51 (86.16)	21.85 (74.22)
Car type			3673.1*** (684.0)
Constant	-6.707 (1174.4)	1946.1 (3597.0)	-5853.7 (3377.0)
Observations	74	74	74

Standard errors in parentheses

\*  $p < 0.05$ , \*\*  $p < 0.01$ , \*\*\*  $p < 0.001$