

Introduction to time-series analysis using Stata

Gustavo Sánchez

StataCorp LLC

August 23, 2022



Outline

TS structure

Stata tools

Date Formats

`import fred`

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

Outline

- Stata tools
- Inputting and managing time series in Stata
 - Date formats in Stata
 - Importing data `import fred`
 - Specifying the time structure and business calendar
 - Time series operators
- Univariate time-series analysis
 - ARIMA models
 - ARCH models
- Multivariate time-series analysis
 - Vector autoregressive (VAR) model
- Forecasting systems of equations

From OLS to Time Series

- Many of the results in OLS and cross-sectional models assume that $\{y_i, x_i\}_{i=1}^n$ are independent draws from the same distribution, like rolling dice n times, i.e, they are independent and identically distributed, i.i.d.
- In time series we are working with draws that depend on each other, e.g. the exchange rate today is not independent from the exchange rate yesterday, for instance.



Stata Tools

- **Data management**
- Univariate time series
 - **ARIMA**, ARFIMA, **ARCH**
 - Prais, Newey, unobserved component model (UCM)
 - Markov-Switching and threshold regressions
 - Time-series smoothers and filters
 - Diagnostic tools
- Multivariate time series.
 - Dynamic factor (dfactor)
 - Multivariate GARCH
 - State space
 - **VAR**, SVAR, VEC models
 - Forecasting, inference, and interpretation
 - Diagnostic tools, graphs and more.
- **Forecasting models**

Managing the time series structure in Stata

Some date formats in Stata

| Format | Description | Coding |
|--------|--------------------|------------------------------|
| %td | daily (same as %d) | 0 = 01jan1960, 1 = 02jan1960 |
| %tw | weekly | 0 = 1960w1, 1 = 1960w2 |
| %tm | monthly | 0 = 1960m1, 1 = 1960m2 |
| %tq | quarterly | 0 = 1960q1, 1 = 1960q2 |
| %th | halfyearly | 0 = 1960h1, 1 = 1960h2 |
| %ty | yearly | 1960 = 1960, 1961 = 1961 |

Note: times before 1960 are allowed. For instance, -1 means 31dec1959 in %td format and 1959q4 in %tq format.

- use **generic** for unformatted time variable
- use **datetime business calendars** for business-day data or other irregular time formats

Example 1: Importing data from FRED

- We can use `import fred` to get data from the Federal Reserve Economic Data (FRED).

```
. import fred SP500 CBBTCUSD VIXCLS, daterange(2017-01-03 2022-08-31)
. rename SP500      sp500
. rename VIXCLS     vix
. rename CBBTCUSD   bitcoin
```

```
. describe
```

Contains data

```
Observations:      2,057
Variables:         5
```

| Variable name | Storage type | Display format | Value label | Variable label |
|----------------------|--------------------|--------------------|-------------|----------------------------|
| <code>datestr</code> | <code>str10</code> | <code>%-10s</code> | | observation date |
| <code>daten</code> | <code>int</code> | <code>%td</code> | | numeric (daily) date |
| <code>sp500</code> | <code>float</code> | <code>%9.0g</code> | | S&P 500 |
| <code>bitcoin</code> | <code>float</code> | <code>%9.0g</code> | | Coinbase Bitcoin |
| <code>vix</code> | <code>float</code> | <code>%9.0g</code> | | CBOE Volatility Index: VIX |

```
Sorted by: datestr
```

Note: Dataset has changed since last saved.

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

import fred: Dialog box

Stata/MP 17.0

File Edit Data Graphics Statistics User Window Help

History

Statistics and Data Science

Stata license: Single-user
Serial number: 1
Licensed to: Gustavo S
StataCorp

Notes:

1. Unicode is supported
2. More than 2 billion observations
3. Maximum number of series is 100

Import Federal Reserve Economic Data

Search FRED

Keywords: S&P 500 Search

☒ Full text ☐ Series ID

Tags: Sources Releases Seasonal Adjustment Frequencies Geography Types Concepts

Sort by: Popularity Descend

| # | ID | Title |
|----|----------------|--|
| 1 | SP500 | S&P 500 |
| 2 | MEHOINUSA67.. | Real Median Household Income in the United States |
| 3 | MEHOINUSA64.. | Median Household Income in the United States |
| 4 | VIXCLS | CBOE S&P 500 3-Month Volatility Index |
| 5 | MEHOINUSCAA.. | Median Household Income in California |
| 6 | STLPSI | St. Louis Fed Financial Stress Index (DISCONTINUED) |
| 7 | MEHOINUSNYA.. | Real Median Household Income in New York |
| 8 | EMVOVERALLE.. | Equity Market Volatility Tracker: Overall |
| 9 | MEHOINUSMIA.. | Real Median Household Income in Michigan |
| 10 | MEHOINUSCAA.. | Real Median Household Income in California |
| 11 | MEHOINUSTX46.. | Real Median Household Income in Texas |
| 12 | EMVMACROBUS | Equity Market Volatility Tracker: Macroeconomic New... |
| 13 | MEHOINUSFLA.. | Real Median Household Income in Florida |
| 14 | MEHOINUSMNA.. | Real Median Household Income in Minnesota |
| 15 | MEHOINUSCOA.. | Real Median Household Income in Colorado |
| 16 | MEHOINUSALA.. | Real Median Household Income in Alabama |
| 17 | MEHOINUSILAB.. | Real Median Household Income in Illinois |
| 18 | MEHOINUSAZA.. | Real Median Household Income in Arizona |
| 19 | MEHOINUSMAA.. | Real Median Household Income in Massachusetts |
| 20 | MEHOINUSOKA.. | Real Median Household Income in Oklahoma |
| 21 | MEHOINUSUTA.. | Real Median Household Income in Utah |
| 22 | MEHOINUSMOA.. | Real Median Household Income in Missouri |
| 23 | MEHOINUSALA.. | Real Median Household Income in Alabama |
| 24 | MEHOINUSKYA.. | Real Median Household Income in Kentucky |

1-153 of 153

Add to filters

Filters:

Remove

Describe Add

Series to import:

| # | Title |
|---|---------|
| 1 | S&P 500 |

Remove Import Cancel

Command Ready

C:\Users\gas\Documents

CAP NUM INS

Calendars and (non)missing data

- Specify the time series structure

```
. tsset daten,daily
```

```
Time variable: daten, 03jan2017 to 21aug2022
```

```
Delta: 1 day
```

- Some processes imply that there is no data for certain periods. For example, Weekends and holidays in daily financial data.
- For some days there is no data, but there are no missing observations on the process

```
. list daten sp500 bitcoin vix in 1/8,sep(4)
```

| | daten | sp500 | bitcoin | vix |
|----|-----------|---------|---------|-------|
| 1. | 03jan2017 | 2257.83 | 1020.67 | 12.85 |
| 2. | 04jan2017 | 2270.75 | 1130.3 | 11.85 |
| 3. | 05jan2017 | 2269 | 1007 | 11.67 |
| 4. | 06jan2017 | 2276.98 | 895.71 | 11.32 |
| 5. | 07jan2017 | . | 909 | . |
| 6. | 08jan2017 | . | 923.33 | . |
| 7. | 09jan2017 | 2268.9 | 902.66 | 11.56 |
| 8. | 10jan2017 | 2268.9 | 907 | 11.49 |

- Use **datetime business calendars**

bcalstocks.stbcal

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

```
version 17
dateformat dmy

range 03jan2017 31aug2022
centerdate 03jan2017

omit dayofweek (Sa Su)
omit date 1jan*
omit date 4jul*
omit downinmonth +3 Mo of jan
omit downinmonth +3 Mo of feb
omit downinmonth -1 Mo of may
omit downinmonth +1 Mo of sep
omit downinmonth +4 Th of Nov
omit date 24dec2021
omit date 25dec*
omit date 14apr2017
omit date 30mar2018
omit date 5dec2018
omit date 19apr2019
omit date 10apr2020
omit date 3jul2020
omit date 2apr2021
omit date 5jul2021
omit date 15apr2022
omit date 20jun2022
```

Business Calendar for the stocks data

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

```
. generate bdate=bofd("bcalstocks",daten)
(639 missing values generated)
```

```
. format bdate %tbbcalstocks
```

```
. tsset bdate
```

Time variable: bdate, 03jan2017 to 19aug2022

Delta: 1 day

```
. drop if bdate==.
```

(639 observations deleted)

```
. list daten bdate sp500 bitcoin vix in 1/8,sep(4)
```

| | daten | bdate | sp500 | bitcoin | vix |
|----|-----------|-----------|---------|---------|-------|
| 1. | 03jan2017 | 03jan2017 | 2257.83 | 1020.67 | 12.85 |
| 2. | 04jan2017 | 04jan2017 | 2270.75 | 1130.3 | 11.85 |
| 3. | 05jan2017 | 05jan2017 | 2269 | 1007 | 11.67 |
| 4. | 06jan2017 | 06jan2017 | 2276.98 | 895.71 | 11.32 |
| 5. | 09jan2017 | 09jan2017 | 2268.9 | 902.66 | 11.56 |
| 6. | 10jan2017 | 10jan2017 | 2268.9 | 907 | 11.49 |
| 7. | 11jan2017 | 11jan2017 | 2275.32 | 795.77 | 11.26 |
| 8. | 12jan2017 | 12jan2017 | 2270.44 | 812.25 | 11.54 |

Preparing your data format with date functions

- Use the `date()` function to convert your string dates to a numerical date
- Use one of the following functions to convert your daily date to your desired frequency
 - `wofd(%td_daily_date_exp)` returns %tw date
 - `mofd(%td_daily_date_exp)` returns %tm date
 - `qofd(%td_daily_date_exp)` returns %tq date
 - `hofd(%td_daily_date_exp)` returns %th date
 - `yofd(%td_daily_date_exp)` returns %ty date
- Then use `tsset` to specify your time variable

Example 2: Passenger car registrations in Chile

- Get data from the Federal Reserve Economic Data (FRED).

```
. import fred CHLSACRQISMEI, daterange(1990-01-01 2010-12-31) ///
>      aggregate(quarterly) clear
```

Summary

| Series ID | Nobs | Date range | Frequency |
|---------------|------|--------------------------|-----------|
| CHLSACRQISMEI | 68 | 1994-01-01 to 2010-10-01 | Quarterly |

```
# of series imported: 1
  highest frequency: Quarterly
  lowest frequency: Quarterly
```

```
.
. rename CHLSACRQISMEI cars_cl
. describe
```

Contains data

```
Observations:      68
Variables:         3
```

| Variable name | Storage type | Display format | Value label | Variable label |
|---------------|--------------|----------------|-------------|--------------------------------------|
| datestr | str10 | %-10s | | observation date |
| daten | int | %td | | numeric (daily) date |
| cars_cl | float | %9.0g | | Passenger Car Registrations in Chile |

```
Sorted by: datestr
```

```
Note: Dataset has changed since last saved.
```

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

import fred: Dialog box

Stata/MP 17.0

File Edit Data Graphics Statistics User Window Help

History

Import Federal Reserve Economic Data

Search FRED

Keywords:

Chile cars

Search

☒ Full text ☐ Series ID

Tags:

- > Sources
- > Releases
- > Seasonal Adjustment
- > Frequencies
 - annual
 - monthly
 - quarterly
- > Geography Types
- > Geographies
- > Concepts

Add to filters

Filters:

Remove

Sort by: Popularity Descend

| # | ID | Title | Frequency |
|----|-----------------|---|-----------|
| 1 | CHLSLRTCR03M... | Sales: Retail trade: Car registration: Passenger cars for .. | Monthly |
| 2 | SLRTR03CLA6... | Retail Trade Sales: Passenger Car Registrations for Chile Annual | Annual |
| 3 | SLRTR03CLQ1... | Retail Trade Sales: Passenger Car Registrations for Chile Quarterly | Quarterly |
| 4 | CHLSACRAISMEI | Passenger Car Registrations in Chile | Annual |
| 5 | CHLSLRTCR03M... | Sales: Retail trade: Car registration: Passenger cars for .. | Monthly |
| 6 | CHLSACRQISMEI | Passenger Car Registrations in Chile | Monthly |
| 7 | SLRTR03CLA1... | Retail Trade Sales: Passenger Car Registrations for Chile Annual | Annual |
| 8 | CHLSLRTCR03G... | Sales: Retail trade: Car registration: Passenger cars for ... | Monthly |
| 9 | CHLSLRTCR03G... | Sales: Retail trade: Car registration: Passenger cars for ... | Monthly |
| 10 | CHLSLRTCR03M... | Sales: Retail trade: Car registration: Passenger cars for ... | Monthly |
| 11 | SLRTR03CLA6... | Retail Trade Sales: Passenger Car Registrations for Chile Annual | Annual |
| 12 | CHLSACRQISMEI | Passenger Car Registrations in Chile | Quarterly |
| 13 | SLRTR03CLA1... | Retail Trade Sales: Passenger Car Registrations for Chile Annual | Annual |
| 14 | SLRTR03CLQ1... | Retail Trade Sales: Passenger Car Registrations for Chile Annual | Annual |
| 15 | SLRTR03CLQ1... | Retail Trade Sales: Passenger Car Registrations for Chile Quarterly | Quarterly |
| 16 | SLRTR03CLQ6... | Retail Trade Sales: Passenger Car Registrations for Chile Quarterly | Quarterly |
| 17 | SLRTR03CLQ6... | Retail Trade Sales: Passenger Car Registrations for Chile Quarterly | Quarterly |
| 18 | SLRTR03CLQ6... | Retail Trade Sales: Passenger Car Registrations for Chile Quarterly | Quarterly |

Series to import:

| # | Title | ID |
|---|--------------------------------------|---------------|
| 1 | Passenger Car Registrations in Chile | CHLSACRQISMEI |

Describe Add

Remove

Import Cancel

Command Ready

C:\Users\gas\Documents\webinars\2022\time_series\do-files

CAP NUM INS

Example 2: Continue (Date functions)

```
. generate quarter = qofd(daten)
. format quarter %tq
.
. /* Specify time-series structure */
. tsset quarter
Time variable: quarter, 1994q1 to 2010q4
Delta: 1 quarter
.
. list daten quarter cars_cl if tin(1994q1,1994q4)
```

| | daten | quarter | cars_cl |
|----|-----------|---------|----------|
| 1. | 01jan1994 | 1994q1 | 39.41069 |
| 2. | 01apr1994 | 1994q2 | 37.96296 |
| 3. | 01jul1994 | 1994q3 | 37.82406 |
| 4. | 01oct1994 | 1994q4 | 38.48565 |

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

- Once you specify the time identifier variable with `tsset`, you can then use time-series operators on the variables
 - L is the lag operator; $Lk.x = x_{t-k}$
 - D is the first-difference operator; $D.x = \Delta x_t = x_t - x_{t-1}$
 - $Dk.x = \Delta^k x_t = \Delta \cdots (\Delta(\Delta x_t)) \cdots$
 - F is lead operator; $Fk.x = x_{t+k}$
 - S is the seasonal-difference operator; $Sk.x = x_t - x_{t-k}$
 - L (*numlist*) . (*varlist*)

```
. list quarter cars_cl L.cars_cl L2.cars_cl F.cars_cl D.cars_cl ///
>      if tin(1994q1,1994q4), noobs
```

| quarter | cars_cl | L. cars_cl | L2. cars_cl | F. cars_cl | D. cars_cl |
|---------|----------|---------------|----------------|---------------|---------------|
| 1994q1 | 39.41069 | . | . | 37.96296 | . |
| 1994q2 | 37.96296 | 39.41069 | . | 37.82406 | -1.447731 |
| 1994q3 | 37.82406 | 37.96296 | 39.41069 | 38.48565 | -.1388969 |
| 1994q4 | 38.48565 | 37.82406 | 37.96296 | 46.53998 | .6615829 |

Time-series operators

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

- Once you specify the time identifier variable with `tsset`, you can then use time-series operators on the variables
 - L is the lag operator; $Lk.x = x_{t-k}$
 - D is the first-difference operator; $D.x = \Delta x_t = x_t - x_{t-1}$
 - $Dk.x = \Delta^k x_t = \Delta \cdots (\Delta(\Delta x_t)) \cdots$
 - F is lead operator; $Fk.x = x_{t+k}$
 - S is the seasonal-difference operator; $Sk.x = x_t - x_{t-k}$
 - $L(numlist) . (varlist)$


```
. list quarter cars_cl L.cars_cl L2.cars_cl F.cars_cl D.cars_cl ///
> if tin(1994q1,1994q4), noobs
```

| quarter | cars_cl | L. cars_cl | L2. cars_cl | F. cars_cl | D. cars_cl |
|---------|----------|---------------|----------------|---------------|---------------|
| 1994q1 | 39.41069 | . | . | 37.96296 | . |
| 1994q2 | 37.96296 | 39.41069 | . | 37.82406 | -1.447731 |
| 1994q3 | 37.82406 | 37.96296 | 39.41069 | 38.48565 | -.1388969 |
| 1994q4 | 38.48565 | 37.82406 | 37.96296 | 46.53998 | .6615829 |

Example 2: Continue (Time-series graphs)

- You can also use the `tsline` command, which recognizes the time structure previously specified with `tsset`:


```
. tsline cars_cl,                                     ///  
>   title("Quarterly total passenger car registrations")  ///  
>   subtitle("Chile 1994q1-2010q4") ytitle(" ") xtitle(" ") ///  
>   note(Source: Federal Reserve databank)
```



Example 1: Continue (Time-series graphs)

- Let's also plot the first difference of the series:

```
. tsline D.cars_cl,  
> title("Quarterly passenger car registrations (First difference)")  
> subtitle("Chile 1994q1-2010q4") ytitle(" ") xtitle(" ")  
> note(Source: Federal Reserve databank)
```



Outline

TS structure

- Stata tools
- Date Formats
- import fred
- Calendars
- TS operators

Univariate models

- ARIMA model
- ARCH model

Multivariate models

- VAR model

Forecast

Summing up

References

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

ARIMA models

ARMA models

- In general, ARIMA models assume that we are working with weakly stationary time series.
- These models can be understood as combinations of white noise ε_t processes (which, in short, are stationary processes with zero mean, constant variance, and covariances that don't depend on t).
- These are the models we are considering here:

$$\text{AR}(1): \quad y_t = \phi y_{t-1} + \varepsilon_t$$

$$\text{MA}(1): \quad y_t = \varepsilon_t + \theta \varepsilon_{t-1}$$

$$\text{AR}(p): \quad y_t = \phi_1 y_{t-1} + \phi_2 y_{t-2} + \cdots + \phi_p y_{t-p} + \varepsilon_t$$

$$\text{MA}(q): \quad y_t = \varepsilon_t + \theta_1 \varepsilon_{t-1} + \theta_2 \varepsilon_{t-2} + \cdots + \theta_q \varepsilon_{t-q}$$

$$\text{ARMA}(p,q): \quad y_t = \phi_1 y_{t-1} + \cdots + \phi_p y_{t-p} + \varepsilon_t + \theta_1 \varepsilon_{t-1} + \cdots + \theta_q \varepsilon_{t-q}$$

ARMA models

Outline

TS structure

Stata tools
Date Formats
import fred
Calendars
TS operators

Univariate
models

ARIMA model
ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

- In general, ARIMA models assume that we are working with weakly stationary time series.
- These models can be understood as combinations of white noise ε_t processes (which, in short, are stationary processes with zero mean, constant variance, and covariances that don't depend on t).
- These are the models we are considering here:

$$\text{AR}(1): \quad y_t = \phi y_{t-1} + \varepsilon_t$$

$$\text{MA}(1): \quad y_t = \varepsilon_t + \theta \varepsilon_{t-1}$$

$$\text{AR}(p): \quad y_t = \phi_1 y_{t-1} + \phi_2 y_{t-2} + \cdots + \phi_p y_{t-p} + \varepsilon_t$$

$$\text{MA}(q): \quad y_t = \varepsilon_t + \theta_1 \varepsilon_{t-1} + \theta_2 \varepsilon_{t-2} + \cdots + \theta_q \varepsilon_{t-q}$$

$$\text{ARMA}(p,q): \quad y_t = \phi_1 y_{t-1} + \cdots + \phi_p y_{t-p} + \varepsilon_t + \theta_1 \varepsilon_{t-1} + \cdots + \theta_q \varepsilon_{t-q}$$

ARMA models

- In general, ARIMA models assume that we are working with weakly stationary time series.
- These models can be understood as combinations of white noise ε_t processes (which, in short, are stationary processes with zero mean, constant variance, and covariances that don't depend on t).
- These are the models we are considering here:

$$\text{AR}(1): \quad y_t = \phi y_{t-1} + \varepsilon_t$$

$$\text{MA}(1): \quad y_t = \varepsilon_t + \theta \varepsilon_{t-1}$$

$$\text{AR}(p): \quad y_t = \phi_1 y_{t-1} + \phi_2 y_{t-2} + \cdots + \phi_p y_{t-p} + \varepsilon_t$$

$$\text{MA}(q): \quad y_t = \varepsilon_t + \theta_1 \varepsilon_{t-1} + \theta_2 \varepsilon_{t-2} + \cdots + \theta_q \varepsilon_{t-q}$$

$$\text{ARMA}(p,q): \quad y_t = \phi_1 y_{t-1} + \cdots + \phi_p y_{t-p} + \varepsilon_t + \theta_1 \varepsilon_{t-1} + \cdots + \theta_q \varepsilon_{t-q}$$

Two Important Concepts

- A time series is $\{y_t\}_{t=1}^T$ **weakly stationary** if $E(y_t)$, $E(y_t^2)$, and $E(y_t y_{t-j})$ do not depend on t .
- For identically distributed and not independent time series, one way to measure the dependence is the autocorrelation function:

$$\rho_l = \frac{\text{Cov}(y_t y_{t-l})}{\text{Var}(y_t)}$$

$$\rho_l = \frac{\text{Cov}(y_t y_{t+l})}{\text{Var}(y_t)}$$

$$\rho_l \equiv \frac{\gamma_l}{\gamma_0}$$

- Another measure is the partial autocorrelation function. It measures the correlation between y_t and y_{t-l} removing the mutual dependence that occurred in the intermediate periods.

Two Important Concepts

- A time series is $\{y_t\}_{t=1}^T$ **weakly stationary** if $E(y_t)$, $E(y_t^2)$, and $E(y_t y_{t-j})$ do not depend on t .
- For identically distributed and not independent time series, one way to measure the dependence is the autocorrelation function:

$$\rho_l = \frac{\text{Cov}(y_t y_{t-l})}{\text{Var}(y_t)}$$

$$\rho_l = \frac{\text{Cov}(y_t y_{t+l})}{\text{Var}(y_t)}$$

$$\rho_l \equiv \frac{\gamma_l}{\gamma_0}$$

- Another measure is the partial autocorrelation function. It measures the correlation between y_t and y_{t-l} removing the mutual dependence that occurred in the intermediate periods.

Example 2: ARIMA model for Passenger car registrations

- Let's use the `corrgram` command to look at the correlogram for `D.cars_cl`:

```
. corrgram D.cars_cl, lags(20)
```

| | | | | | -1 | 0 | 1 | -1 | 0 | 1 |
|----|-----|---------|---------|--------|--------|-------------------|---|-------------------|---|---|
| | LAG | AC | PAC | Q | Prob>Q | [Autocorrelation] | | [Partial autocor] | | |
| 1 | | 0.3851 | 0.4003 | 10.388 | 0.0013 | | | | | |
| 2 | | 0.1556 | 0.0117 | 12.111 | 0.0023 | | | | | |
| 3 | | -0.0876 | -0.1742 | 12.665 | 0.0054 | | | | | |
| 4 | | -0.2105 | -0.1701 | 15.916 | 0.0031 | | | | | |
| 5 | | -0.1665 | -0.0143 | 17.983 | 0.0030 | | | | | |
| 6 | | -0.1755 | -0.1617 | 20.317 | 0.0024 | | | | | |
| 7 | | -0.1792 | -0.2584 | 22.792 | 0.0019 | | | | | |
| 8 | | -0.0524 | -0.0521 | 23.007 | 0.0034 | | | | | |
| 9 | | 0.1178 | 0.3449 | 24.113 | 0.0041 | | | | | |
| 10 | | 0.1141 | 0.1567 | 25.17 | 0.0050 | | | | | |
| 11 | | 0.1257 | 0.0633 | 26.475 | 0.0055 | | | | | |
| 12 | | 0.0403 | -0.0801 | 26.611 | 0.0088 | | | | | |
| 13 | | -0.0303 | -0.1055 | 26.69 | 0.0137 | | | | | |
| 14 | | -0.0219 | -0.0203 | 26.732 | 0.0209 | | | | | |
| 15 | | -0.0351 | 0.0194 | 26.841 | 0.0301 | | | | | |
| 16 | | -0.1297 | -0.3395 | 28.367 | 0.0286 | | | | | |
| 17 | | 0.0119 | 0.1622 | 28.38 | 0.0407 | | | | | |
| 18 | | 0.0189 | 0.0500 | 28.414 | 0.0560 | | | | | |
| 19 | | -0.0014 | -0.2319 | 28.414 | 0.0758 | | | | | |
| 20 | | 0.0002 | -0.3739 | 28.414 | 0.0999 | | | | | |

Example 2: Continue (Model selection)

- Let's fit a couple of models (AR1 and MA1) for D.cars_cl:

```
. arima D.cars_cl,ar(1)
. estimates store Model_AR1
. arima D.cars_cl,ma(1)
. estimates store Model_MA1
. /* Output omitted */
```

- And we now look at a summary table of the two models:

```
. estimates table Model_AR1 Model_MA1, star stats(aic bic) b(%9.2f)
```

| Variable | Model_AR1 | Model_MA1 |
|-------------------|-----------|-----------|
| cars_cl | | |
| _cons | 1.25 | 1.21 |
| ARMA | | |
| ar | | |
| L1. | 0.39*** | |
| ma | | |
| L1. | | 0.33** |
| sigma | | |
| _cons | 6.07*** | 6.17*** |
| Statistics | | |
| aic | 438.06 | 440.13 |
| bic | 444.67 | 446.74 |

Legend: * p<0.05; ** p<0.01; *** p<0.001

Example 2: Continue (Final model)

- We now fit the selected model (AR1):

```
. arima D.cars_cl,ar(1) nolog
```

ARIMA regression

Sample: 1994q2 thru 2010q4

Log likelihood = -216.0282

Number of obs = 67

Wald chi2(1) = 17.27

Prob > chi2 = 0.0000

| D.cars_cl | OPG | | | | | |
|-----------|-------------|-----------|----------|-------|----------------------|--------------------|
| | Coefficient | std. err. | z | P> z | [95% conf. interval] | |
| cars_cl | | | | | | |
| | _cons | 1.247205 | 1.410933 | 0.88 | 0.377 | -1.518172 4.012582 |
| ARMA | | | | | | |
| | ar L1. | .3948356 | .0950154 | 4.16 | 0.000 | .2086088 .5810624 |
| /sigma | | 6.074494 | .3603246 | 16.86 | 0.000 | 5.368271 6.780717 |

Note: The test of the variance against zero is one sided, and the two-sided confidence interval is truncated at zero.

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate models

ARIMA model

ARCH model

Multivariate models

VAR model

Forecast

Summing up

References

Outline

TS structure

Stata tools

Date Formats

`import fred`

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

Autoregressive conditional heteroskedasticity

Conditional Heteroskedasticity

- So far we have not modelled variances explicitly. In the stationary case we assumed they were constant.
- Evidently, time series experience different degrees of volatility in different periods.
- It is important not only to model the mean but the variance of a time series.
- Autoregressive conditional heteroskedasticity models capture this idea.

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

- The general framework can be written as:

$$y_t = x_t\beta + \text{ARMA}(p, q) + \varepsilon_t$$

$$\text{Var}(\sigma_t^2) = \gamma_0 + A(\sigma, \varepsilon) + B(\sigma, \varepsilon)^2$$

- The original ARCH(m) model was written as:

$$y_t = x_t\beta + \varepsilon_t$$

$$\sigma_t^2 = \gamma_0 + \gamma_1\varepsilon_{t-1}^2 + \gamma_2\varepsilon_{t-2}^2 + \dots + \gamma_m\varepsilon_{t-m}^2$$

- The original GARCH(m,k) model is given by:

$$y_t = x_t\beta + \varepsilon_t$$

$$\sigma_t^2 = \gamma_0 + \gamma_1\varepsilon_{t-1}^2 + \gamma_2\varepsilon_{t-2}^2 + \dots + \gamma_m\varepsilon_{t-m}^2 + \delta_1\sigma_{t-1}^2 + \delta_2\sigma_{t-2}^2 + \dots + \delta_k\sigma_{t-k}^2$$

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

- The general framework can be written as:

$$y_t = x_t\beta + \text{ARMA}(p, q) + \varepsilon_t$$

$$\text{Var}(\sigma_t^2) = \gamma_0 + A(\sigma, \varepsilon) + B(\sigma, \varepsilon)^2$$

- The original ARCH(m) model was written as:

$$y_t = x_t\beta + \varepsilon_t$$

$$\sigma_t^2 = \gamma_0 + \gamma_1\varepsilon_{t-1}^2 + \gamma_2\varepsilon_{t-2}^2 + \dots + \gamma_m\varepsilon_{t-m}^2$$

- The original GARCH(m,k) model is given by:

$$y_t = x_t\beta + \varepsilon_t$$

$$\sigma_t^2 = \gamma_0 + \gamma_1\varepsilon_{t-1}^2 + \gamma_2\varepsilon_{t-2}^2 + \dots + \gamma_m\varepsilon_{t-m}^2 + \delta_1\sigma_{t-1}^2 + \delta_2\sigma_{t-2}^2 + \dots + \delta_k\sigma_{t-k}^2$$

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

- The general framework can be written as:

$$y_t = x_t\beta + \text{ARMA}(p, q) + \varepsilon_t$$

$$\text{Var}(\sigma_t^2) = \gamma_0 + A(\sigma, \varepsilon) + B(\sigma, \varepsilon)^2$$

- The original ARCH(m) model was written as:

$$y_t = x_t\beta + \varepsilon_t$$

$$\sigma_t^2 = \gamma_0 + \gamma_1\varepsilon_{t-1}^2 + \gamma_2\varepsilon_{t-2}^2 + \dots + \gamma_m\varepsilon_{t-m}^2$$

- The original GARCH(m,k) model is given by:

$$y_t = x_t\beta + \varepsilon_t$$

$$\sigma_t^2 = \gamma_0 + \gamma_1\varepsilon_{t-1}^2 + \gamma_2\varepsilon_{t-2}^2 + \dots + \gamma_m\varepsilon_{t-m}^2 + \delta_1\sigma_{t-1}^2 + \delta_2\sigma_{t-2}^2 + \dots + \delta_k\sigma_{t-k}^2$$

Example 3: ARCH model for Mexican Pesos to U.S. Dollar

- Get data from the Federal Reserve Economic Data (FRED).

```
. import fred EXMXUS, daterange(2000-01-01 2022-08-15)
```

Summary

| Series ID | Nobs | Date range | Frequency |
|-----------|------|--------------------------|-----------|
| EXMXUS | 271 | 2000-01-01 to 2022-07-01 | Monthly |

```
# of series imported: 1
highest frequency: Monthly
lowest frequency: Monthly
```

```
.
. generate month=mofd(daten)
. label var month "numeric (monthly) date"
. rename EXMXUS exchrates_mx
```

```
.
. tsset month,monthly
Time variable: month, 2000m1 to 2022m7
Delta: 1 month
```


```
.
. list in 1/4,abbreviate(12)
```

| | datestr | daten | exchrates_mx | month |
|----|------------|-----------|--------------|--------|
| 1. | 2000-01-01 | 01jan2000 | 9.4935 | 2000m1 |
| 2. | 2000-02-01 | 01feb2000 | 9.4265 | 2000m2 |
| 3. | 2000-03-01 | 01mar2000 | 9.2886 | 2000m3 |
| 4. | 2000-04-01 | 01apr2000 | 9.3937 | 2000m4 |

Example 3: Continue (Time-series graph)

- You can combine two `tsline` graphs to plot the levels and first difference of the exchange rate series:


```
. tsline exchrte_mx, name(level,replace) ytitle(level) xtitle("")
. tsline D.exchrte_mx, name(difference,replace) ///
> ytitle(First difference) xtitle("month")
. graph combine level difference, rows(2) ///
> title("Mexican pesos to US dollar") ///
> note(Source: Federal Reserve databank)
```



Example 3: (Continue)

- Use `ac` and `pac` to look at the autocorrelation and partial autocorrelation functions for `dexchrte_mx`:

```
. ac D.exchrte_mx, lags(25) ytitle(" ") name(ac_dexchrte_mx) ///
> title("Autocorrelation function for D.exchrte_mx")
. pac D.exchrte_mx, lags(25) ytitle(" ") name(pac_dexchrte_mx) ///
> title("Partial autocorrelation function for D.exchrte_mx")
.
. graph combine ac_dexchrte_mx pac_dexchrte_mx, rows(2)
```



Example 3: Model selection from three alternative specifications:

```
. arch D.exchrates_mx,arch(1) garch(1) ar(1/2) nolog
. estimates store arch_ar1_2
. arch D.exchrates_mx,arch(1) garch(1) ma(1) nolog
. estimates store arch_ma1
. arch D.exchrates_mx,arch(1) garch(1) ma(1) ar(1/2) nolog
. estimates store arch_arma

. estimates table arch_ar1_2 arch_ma1 arch_arma, ///
> star stats(aic bic) b(%9.2f) vsquish
```

| Variable | arch_ar1_2 | arch_ma1 | arch_arma |
|-----------------------|------------|----------|-----------|
| exchrates_mx _cons | 0.05 | 0.05 | 0.04 |
| ARMA | | | |
| ar | | | |
| L1. | 0.37*** | | 0.83** |
| L2. | -0.20* | | -0.34** |
| ma | | | |
| L1. | | 0.33*** | -0.48 |
| ARCH | | | |
| arch | | | |
| L1. | 0.10*** | 0.10*** | 0.11*** |
| garch | | | |
| L1. | 0.91*** | 0.91*** | 0.91*** |
| _cons | 0.00** | 0.00** | 0.00** |
| Statistics | | | |
| aic | 257.92 | 260.33 | 257.25 |
| bic | 279.51 | 278.33 | 282.44 |

Legend: * p<0.05; ** p<0.01; *** p<0.001

Example 3: Continue (Final ARCH model)

- We now fit the selected model:

```
. arch D.exchrates_mx, arch(1) garch(1) ar(1/2) nolog vsquish
```

ARCH family regression -- AR disturbances

Sample: 2000m2 thru 2022m7

Number of obs = 270

Wald chi2(2) = 20.63

Prob > chi2 = 0.0000

Log likelihood = -122.9579

| D. | OPG | | | | | |
|--------------|-------------|-----------|-------|-------|----------------------|-----------|
| exchrates_mx | Coefficient | std. err. | z | P> z | [95% conf. interval] | |
| exchrates_mx | | | | | | |
| _cons | .0474618 | .0302807 | 1.57 | 0.117 | -.0118872 | .1068108 |
| ARMA | | | | | | |
| ar | | | | | | |
| L1. | .3713764 | .087179 | 4.26 | 0.000 | .2005087 | .5422441 |
| L2. | -.1954443 | .0765553 | -2.55 | 0.011 | -.34549 | -.0453987 |
| ARCH | | | | | | |
| arch | | | | | | |
| L1. | .100711 | .0234196 | 4.30 | 0.000 | .0548095 | .1466125 |
| garch | | | | | | |
| L1. | .91257 | .0113487 | 80.41 | 0.000 | .8903269 | .9348132 |
| _cons | .0020402 | .0006335 | 3.22 | 0.001 | .0007986 | .0032819 |

Outline

TS structure

Stata tools

Date Formats

`import fred`

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast

Summing up

References

Vector autoregressive (VAR) model

Vector Autoregressive Models VAR

- VARs are extensions of AR(p) models for vector valued dependent variables with no structural form.
- A VAR model can be written as:

$$\mathbf{y}_t = \mathbf{v} + \mathbf{A}_1 \mathbf{y}_{t-1} + \dots + \mathbf{A}_p \mathbf{y}_{t-p} + \mathbf{C}_0 \mathbf{x}_t + \mathbf{C}_1 \mathbf{x}_{t-1} + \dots + \mathbf{C}_s \mathbf{x}_{t-s} + \mathbf{u}_t$$

Where:

$\mathbf{y}_t = (y_{1t}, \dots, y_{Kt})$ is a $K \times 1$ random vector

\mathbf{A}_1 through \mathbf{A}_p are $K \times K$ matrices of parameters.

\mathbf{x}_t is an $M \times 1$ vector of exogenous variables

\mathbf{C}_0 through \mathbf{C}_s are $K \times M$ matrices of parameters.

\mathbf{v} is a $K \times 1$ vector of parameters

\mathbf{u}_t is a vector assumed to be white noise:

$$E(\mathbf{u}_t) = \mathbf{0}$$

$$E(\mathbf{u}_t \mathbf{u}_t') = \mathbf{\Sigma}$$

$$E(\mathbf{u}_t \mathbf{u}_s') = \mathbf{0} ; t \neq s$$

- The number of coefficients is quadratic to the number of dependent variables and proportional the number of lags.

Example 4: Vector autoregressive (VAR) model for stock data

- We use `import fred` to get data from the Federal Reserve Economic Data (FRED).

```
. import fred SP500 CBBTCUSD VIXCLS, daterange(2017-01-02 .) ///
>   aggregate(weekly,avg) clear
. rename SP500 sp500
. rename CBBTCUSD bitcoin
. rename VIXCLS vix
```

```
. describe
```

Contains data

Observations: 295

Variables: 5

| Variable name | Storage type | Display format | Value label | Variable label |
|----------------|--------------|----------------|-------------|----------------------------|
| datestr | str10 | %-10s | | observation date |
| daten | int | %td | | numeric (daily) date |
| sp500 | float | %9.0g | | S&P 500 |
| bitcoin | float | %9.0g | | Coinbase Bitcoin |
| vix | float | %9.0g | | CBOE Volatility Index: VIX |

Sorted by: datestr

Note: Dataset has changed since last saved.


```
.
. tsset daten,delta(7 days)
```

Time variable: daten, 06jan2017 to 26aug2022

Delta: 7 days

Endogenous variables for VAR model

```
. tsline sp500,name(sp_levels,replace) ytitle("Levels")          ///
>   title("S&P 500") ylabel(#3,angle(0)) xlabel(#3) xtitle("")
. tsline D.sp500,name(sp_diff,replace) ytitle("First difference")  ///
>   ylabel(#3,angle(0)) xlabel(#3) xtitle("")
. tsline bitcoin,name(bitcoin_levels,replace) ytitle("Levels")      ///
>   title("Coinbase Bitcoin") ylabel(#3,angle(0)) xlabel(#3) xtitle("")
. tsline D.sp500,name(bitcoin_diff,replace) ytitle("First difference") ///
>   ylabel(#3,angle(0)) xlabel(#3) xtitle("")
.
. graph combine sp_levels bitcoin_levels sp_diff bitcoin_diff,rows(2)  ///
>   note(Source: Federal Reserve databank)
```



Exogenous variable for VAR model

Outline

TS structure

Stata tools

Date Formats

import fred

Calendars

TS operators

Univariate
models

ARIMA model

ARCH model

Multivariate
models

VAR model

Forecast


Summing up

References

```

. tsline vix,name(vix_levels,replace) ytitle("Levels")
. tsline D.vix,name(vix_diff,replace) ytitle("First difference")
.
. graph combine vix_levels vix_diff,          ///
> title("Weekly CBOE Volatility Index: VIX")      ///
> note(Source: Federal Reserve databank) rows(2)

```



VAR model for S&P500 and Bitcoin with exogenous VIX variable

Outline

TS structure

- Stata tools
- Date Formats
- import fred
- Calendars
- TS operators

Univariate
models

- ARIMA model
- ARCH model

Multivariate
models

- VAR model

Forecast

Summing up

References

```
. var D.sp500 D.bitcoin if tin(06mar2020,19aug2022), exog(D.vix) vsquish
```

Vector autoregression

| | | | | | | |
|----------------|-----------|-----------|-----------|---------------|----------|-----|
| Sample: | 06mar2020 | thru | 19aug2022 | Number of obs | = | 129 |
| Log likelihood | = | -1887.785 | AIC | = | 29.45404 | |
| FPE | = | 2.12e+10 | HQIC | = | 29.56213 | |
| Det (Sigma_ml) | = | 1.76e+10 | SBIC | = | 29.72007 | |


| Equation | Parms | RMSE | R-sq | chi2 | P>chi2 |
|-----------|-------|---------|--------|----------|--------|
| D_sp500 | 6 | 52.1009 | 0.6578 | 248.0081 | 0.0000 |
| D_bitcoin | 6 | 2828.93 | 0.1556 | 23.76526 | 0.0002 |

| | Coefficient | Std. err. | z | P> z | [95% conf. interval] | |
|-----------|-------------|-----------|--------|-------|----------------------|-----------|
| D_sp500 | | | | | | |
| sp500 | | | | | | |
| LD. | .1722277 | .0550092 | 3.13 | 0.002 | .0644116 | .2800437 |
| L2D. | .0567062 | .0552017 | 1.03 | 0.304 | -.0514871 | .1648995 |
| bitcoin | | | | | | |
| LD. | -.0011056 | .0016788 | -0.66 | 0.510 | -.004396 | .0021849 |
| L2D. | .0017677 | .0016631 | 1.06 | 0.288 | -.001492 | .0050275 |
| vix | | | | | | |
| D1. | -16.62902 | 1.120476 | -14.84 | 0.000 | -18.82511 | -14.43292 |
| _cons | 6.235951 | 4.497384 | 1.39 | 0.166 | -2.578759 | 15.05066 |
| D_bitcoin | | | | | | |
| sp500 | | | | | | |
| LD. | 3.637138 | 2.986841 | 1.22 | 0.223 | -2.216963 | 9.491239 |
| L2D. | -2.475878 | 2.997291 | -0.83 | 0.409 | -8.350461 | 3.398705 |
| bitcoin | | | | | | |
| LD. | .2891966 | .0911558 | 3.17 | 0.002 | .1105346 | .4678586 |
| L2D. | -.0539655 | .0903042 | -0.60 | 0.550 | -.2309585 | .1230275 |
| vix | | | | | | |
| D1. | -154.3945 | 60.83859 | -2.54 | 0.011 | -273.6359 | -35.15304 |
| _cons | 61.27406 | 244.1949 | 0.25 | 0.802 | -417.3392 | 539.8873 |

```
. estimates store eq_var
```

Impulse-response functions

```
. irf create order1, step(10) set(myirf1,replace)
. irf graph oirf
. irf graph oirf, impulse(D.bitcoin) response(D.sp500) name(i_bit__r_sp)
. irf graph oirf, impulse(D.bitcoin) response(D.bitcoin) name(i_bit__r_bit)
. irf graph oirf, impulse(D.sp500) response(D.sp500) name(i_sp__r_sp)
. irf graph oirf, impulse(D.sp500) response(D.bitcoin) name(i_sp__r_bit)
.
. graph combine i_bit__r_sp i_bit__r_bit i_sp__r_sp i_sp__r_bit, ///
> title("Impulse-response functions")
```



Solving and forecasting systems of equations

Solving models for a collection of equations

- Components
 - Stochastic equations fit using estimation commands
 - Identities
 - Coefficient vectors
- Solving the model
 - Obtain static or dynamic forecasts
 - Alternative forecast scenarios
- `forecast` command

forecast subcommands

- Building the model
 - create
 - estimates
 - identity
 - coefvector
 - exogenous
- Solving the model
 - solve
 - adjust
- Utilities
 - describe
 - list
 - clear
 - drop
 - query

Example 5: System of equations VAR and ARIMA

- We now combine the results for the VAR model in example 4 with an ARIMA model for the exogenous variable vix.
- Let's fit an ARIMA model for vix and store the results:

```
. arima D.vix if tin(06mar2020,19aug2022), ar(1) nolog
```

ARIMA regression

Sample: 06mar2020 thru 19aug2022

Number of obs = 129

Wald chi2(1) = 28.33

Prob > chi2 = 0.0000

Log likelihood = -359.4667

| | D.vix | OPG | | | | |
|-------------|--------|-------------|-----------|-------|-------|----------------------|
| | | Coefficient | std. err. | z | P> z | [95% conf. interval] |
| vix | | | | | | |
| | _cons | -.0823354 | .5566037 | -0.15 | 0.882 | -1.173259 1.008588 |
| ARMA | | | | | | |
| | ar | | | | | |
| | L1. | .2379425 | .0447051 | 5.32 | 0.000 | .1503222 .3255629 |
| | /sigma | 3.925202 | .1242906 | 31.58 | 0.000 | 3.681597 4.168807 |

Note: The test of the variance against zero is one sided, and the two-sided confidence interval is truncated at zero.

```
.  
. estimates store eq_ar1
```

Example 5: Continue

- Use the suite of `forecast` commands to solve the model.

```
. tsappend, add(4)
. forecast create myforecast
Forecast model myforecast started.
. forecast estimates eq_var,names(dsp500 dbitcoin)
Added estimation results from var.
Forecast model myforecast now contains 2 endogenous variables.
. forecast estimates eq_ar1,names(dvix)
Added estimation results from arima.
Forecast model myforecast now contains 3 endogenous variables.
. forecast identity sp500=dsp500+L.sp500
Forecast model myforecast now contains 4 endogenous variables.
. forecast identity bitcoin=dbitcoin+L.bitcoin
Forecast model myforecast now contains 5 endogenous variables.
. forecast identity vix=dvix+L.vix
Forecast model myforecast now contains 6 endogenous variables.
. forecast solve, begin(td(26aug2022)) end(td(16sep2022)) prefix(f_)
Computing dynamic forecasts for model myforecast.
```

```
Starting period: 26aug2022
Ending period: 16sep2022
Forecast prefix: f_


26aug2022: .....
02sep2022: .....
09sep2022: .....
16sep2022: .....
Forecast 6 variables spanning 4 periods.
```

Example 5: Continue

- Let's look at the forecasts for the next 4 weeks.

```
. list daten sp500 f_sp500 bitcoin f_bitcoin vix f_vix ///
> if tin(29jul2022,16sep2022), noobs
```

| daten | sp500 | f_sp500 | bitcoin | f_bitc_n | vix | f_vix |
|-----------|---------|----------|----------|----------|-------|----------|
| 29jul2022 | 4022.84 | 4022.84 | 22607.86 | 22607.86 | 22.99 | 22.99 |
| 05aug2022 | 4132.42 | 4132.42 | 23129.3 | 23129.3 | 22.26 | 22.26 |
| 12aug2022 | 4192.04 | 4192.04 | 23635.53 | 23635.53 | 20.51 | 20.51 |
| 19aug2022 | 4277.72 | 4277.72 | 23440.96 | 23440.96 | 19.94 | 19.94 |
| 26aug2022 | . | 4306.502 | . | 23613.29 | . | 19.74163 |
| 02sep2022 | . | 4323.848 | . | 23644.43 | . | 19.63168 |
| 09sep2022 | . | 4336.452 | . | 23710.96 | . | 19.54278 |
| 16sep2022 | . | 4347.219 | . | 23805.65 | . | 19.45888 |



Summing up

- Stata tools
- Inputting and managing time series in Stata
- Univariate time-series analysis
 - ARIMA models
 - ARCH models
- Multivariate time-series analysis with
 - Vector autoregressive (VAR) model
- Forecasting systems of equations

Proceedings for presentations on time series using Stata

- Technical tips on time series with Stata:

<https://www.stata.com/meeting/mexico11/materials/gsanchez.pdf>

- Cointegrating VAR and probability forecasting:

<https://www.stata.com/meeting/spain12/abstracts/materials/Sanchez.pdf>

- Forecasting tools in Stata

https://www.stata.com/meeting/mexico13/abstracts/materials/mex13_sanchez_forecast.pdf

- Markov-switching regression models in Stata

https://www.stata.com/meeting/spain15/abstracts/materials/spain15_sanchez.pdf

- Bayesian VAR models in Stata:

https://www.stata.com/meeting/mexico21/slides/Mexico21_Sanchez.pdf